

4MAX PRO H SERIES - HARDWARE COMPRESSION

Type	Pro H NovaStar			Pro H VideoStar			
Model	MAX120CPH-4	MAX240CPH-8	MAX480CPH-16	MAX480H-16	MAX960H-32	MAX1440H-48	MAX1920H-64
Camera Input	4 Channel	8 Channel	16 Channel	16 Channel	32 Channel	48 Channel	64 Channel
Display Speed	120 fps	240 fps	480 fps	480 fps	960 fps	1440 fps	1920 fps
Recording Speed	True 120 fps @720 lines res	True 240 fps @720 lines res	True 480 fps @720 lines res	480 fps	960 fps	1440 fps	1920 fps
Playback	True 120 fps @720 lines res	True 240 fps @720 lines res	True 480 fps @720 lines res	480 fps	960 fps	1440 fps	1920 fps
Screens	1 to 4	1 to 8	1 to 16	1 to 16	1 to 32	1 to 48	1 to 64
Monitor Out	VGA & Composite						
Audio Output	4 Channels	8 Channels	16 Channels	16 Channels	32 Channels	48 Channels	64 Channels
Sensor Input	Optional						
Relay Output	Optional						
Video Resolution	720x640, 640x480, 360x240			704x480, 704x240, 320x240			
Quality Control	5 Level (Low to High)						
Video Compression	MPEG-4 Compression						
Playback Display	Multi-Camera Playback						
Network	LAN/Cable/DSL						
Watchdog	Software						
Remote Viewing	Client Viewer or Web Browser						
PTZ Control	RS232 (Pan/Tilt/Zoom/Iris) Optional						
CPU	Intel Dual-Core		Intel Core2Duo				
RAM	256MB	512MB	1GB			2GB	
Hard Disk	320GB	500GB	1TB (Terabyte)	1 TB (Terabyte)	2TB (Terabyte)	3TB (Terabyte)	4TB (Terabyte)
Motherboard	Intel Chipset						
Network Adaptor	10/100/1000 Mbps RJ45						
Modem	56.6k V.90 (Optional)						
5 TV Spot Outs	1 - Fixed, 4 - Programmable (Optional)			N/A			
Case	Rack Mount						
O/S	Windows XP						
Back-Up Device	CD-RW (DVD-RW Optional)						